## City of Carmel Meter Pit and Service Line Specifications - 3/4" and 1" Meters Approved Material List 3/05 st 03/07

Item #	Description	5/8" x 3/4" meters	1" r
1	Meter Pit Cover	Ford C3t	For
	with hole for touch read	Tyler 6150	Ves
	and Plug ( Plug can be Cast or Plastic )		A.Y
		A.Y. McDonald 74M3CTP	
2	Yoke	Ford Y502	For
		Mueller H5020-203	Mul
		A.Y.McDonald 14-2	A.Y
3	Street Side Angle Valve	Ford AV94-323WQ	For
		A.Y.McDonald 4602Y-Q23/4X02	A.Y
		Mueller b14273	Mue
4	House Side Angle Check Valve	Ford HHA94-323Q	For
		Mueller H14245	A.Y
		A.Y.McDonald 12-3YQ33	No
_			_
5	Meter Pit	Fratco HDPE	Fra
		20"w X 48"d	24"
		Mid State-Soniloc	Mid
	1	20"w X 48"d	24"
		0/4846	
6	Service Line	3/4" K Copper	1" K
7	Corporation Stop	Mueller H-15008 3/4"	Mue
		A.Y.McDonald 47010 3/4"	A.Y
		Ford F1000-3Q	For

## **NOTES:**

<sup>\*</sup>Should meter pit need raised to grade, a Mid State Meter Box Extension should be used. No me be raised more than 6", without approval from Carmel Utilities. USING BRICKS OR CEMENT BL NOT AN APPROVED METHOD OF RAISING A METER PIT.

<sup>\*</sup>Should the meter lid need raised it should be done with a Ford Elevator Ring Part #ER15CX or E

<sup>\*</sup>Service lines require compression fittings only. No Pack Joints Allowed (No fittings should Must have a continuous piece of copper from meter to at least 5ft. outside Meter Pit, on house si

<sup>\*</sup>There shall be no buried joints or couplings, except for the corporation stop on the water

\*No pit shall be installed in a traffic area, such as a driveway or sidewalk.

\*The meter pit is to be installed just off the utility easement, on private property. In the middle of th 5ft. Left or Right of Center, As close to easment line as possible.

\*there will be a re-inspection fee for each additional inspection needed

\*METER PIT LID GRADE SHALL BE FLUSH WITH THE GROUND. (HOMEOWNER SHOULD BE ABLE TO MOW OVER LID)